

1 AN ACT concerning transportation.

2 **Be it enacted by the People of the State of Illinois,**
3 **represented in the General Assembly:**

4 Section 5. The Illinois Vehicle Code is amended by changing
5 Section 15-111 as follows:

6 (625 ILCS 5/15-111) (from Ch. 95 1/2, par. 15-111)

7 Sec. 15-111. Wheel and axle loads and gross weights.

8 (a) No vehicle or combination of vehicles with pneumatic
9 tires may be operated, unladen or with load, when the total
10 weight on the road surface exceeds the following: 20,000 pounds
11 on a single axle; 34,000 pounds on a tandem axle with no axle
12 within the tandem exceeding 20,000 pounds; 80,000 pounds gross
13 weight for vehicle combinations of 5 or more axles; or a total
14 weight on a group of 2 or more consecutive axles in excess of
15 that weight produced by the application of the following
16 formula: $W = 500 \text{ times the sum of } (LN \text{ divided by } N-1) + 12N +$
17 36 , where "W" equals overall total weight on any group of 2 or
18 more consecutive axles to the nearest 500 pounds, "L" equals
19 the distance measured to the nearest foot between extremes of
20 any group of 2 or more consecutive axles, and "N" equals the
21 number of axles in the group under consideration.

22 The above formula when expressed in tabular form results in
23 allowable loads as follows:

1	Distance measured					
2	to the nearest					
3	foot between the					
4	extremes of any		Maximum weight in pounds			
5	group of 2 or		of any group of			
6	more consecutive		2 or more consecutive axles			
7	axles					
8	feet	2 axles	3 axles	4 axles	5 axles	6 axles
9	4	34,000				
10	5	34,000				
11	6	34,000				
12	7	34,000				
13	8	38,000*	42,000			
14	9	39,000	42,500			
15	10	40,000	43,500			
16	11		44,000			
17	12		45,000	50,000		
18	13		45,500	50,500		
19	14		46,500	51,500		
20	15		47,000	52,000		
21	16		48,000	52,500	58,000	
22	17		48,500	53,500	58,500	
23	18		49,500	54,000	59,000	
24	19		50,000	54,500	60,000	
25	20		51,000	55,500	60,500	66,000

1	21	51,500	56,000	61,000	66,500
2	22	52,500	56,500	61,500	67,000
3	23	53,000	57,500	62,500	68,000
4	24	54,000	58,000	63,000	68,500
5	25	54,500	58,500	63,500	69,000
6	26	55,500	59,500	64,000	69,500
7	27	56,000	60,000	65,000	70,000
8	28	57,000	60,500	65,500	71,000
9	29	57,500	61,500	66,000	71,500
10	30	58,500	62,000	66,500	72,000
11	31	59,000	62,500	67,500	72,500
12	32	60,000	63,500	68,000	73,000
13	33		64,000	68,500	74,000
14	34		64,500	69,000	74,500
15	35		65,500	70,000	75,000
16	36		66,000	70,500	75,500
17	37		66,500	71,000	76,000
18	38		67,500	72,000	77,000
19	39		68,000	72,500	77,500
20	40		68,500	73,000	78,000
21	41		69,500	73,500	78,500
22	42		70,000	74,000	79,000
23	43		70,500	75,000	80,000
24	44		71,500	75,500	
25	45		72,000	76,000	
26	46		72,500	76,500	

1	47	73,500	77,500
2	48	74,000	78,000
3	49	74,500	78,500
4	50	75,500	79,000
5	51	76,000	80,000
6	52	76,500	
7	53	77,500	
8	54	78,000	
9	55	78,500	
10	56	79,500	
11	57	80,000	

12 *If the distance between 2 axles is 96 inches or less, the 2
13 axles are tandem axles and the maximum total weight may not
14 exceed 34,000 pounds, notwithstanding the higher limit
15 resulting from the application of the formula.

16 Vehicles not in a combination having more than 4 axles may
17 not exceed the weight in the table in this subsection (a) for 4
18 axles measured between the extreme axles of the vehicle.

19 Vehicles in a combination having more than 6 axles may not
20 exceed the weight in the table in this subsection (a) for 6
21 axles measured between the extreme axles of the combination.

22 Local authorities, with respect to streets and highways
23 under their jurisdiction, without additional fees, may also by
24 ordinance or resolution allow the weight limitations of this
25 subsection, provided the maximum gross weight on any one axle
26 shall not exceed 20,000 pounds and the maximum total weight on

1 any tandem axle shall not exceed 34,000 pounds, on designated
2 highways when appropriate regulatory signs giving notice are
3 erected upon the street or highway or portion of any street or
4 highway affected by the ordinance or resolution.

5 The following are exceptions to the above formula:

6 (1) Vehicles for which a different limit is established
7 and posted in accordance with Section 15-316 of this Code.

8 (2) Vehicles for which the Department of
9 Transportation and local authorities issue overweight
10 permits under authority of Section 15-301 of this Code.
11 These vehicles are not subject to the bridge formula.

12 (3) Cities having a population of more than 50,000 may
13 permit by ordinance axle loads on 2 axle motor vehicles 33
14 1/2% above those provided for herein, but the increase
15 shall not become effective until the city has officially
16 notified the Department of the passage of the ordinance and
17 shall not apply to those vehicles when outside of the
18 limits of the city, nor shall the gross weight of any 2
19 axle motor vehicle operating over any street of the city
20 exceed 40,000 pounds.

21 (4) Weight limitations shall not apply to vehicles
22 (including loads) operated by a public utility when
23 transporting equipment required for emergency repair of
24 public utility facilities or properties or water wells.

25 (5) Two consecutive sets of tandem axles may carry a
26 total weight of 34,000 pounds each if the overall distance

1 between the first and last axles of the consecutive sets of
2 tandem axles is 36 feet or more, notwithstanding the lower
3 limit resulting from the application of the above formula.

4 (6) A truck, not in combination and used exclusively
5 for the collection of rendering materials, may, when laden,
6 transmit upon the road surface, except when on part of the
7 National System of Interstate and Defense Highways, the
8 following maximum weights: 22,000 pounds on a single axle;
9 40,000 pounds on a tandem axle.

10 (7) A truck not in combination, equipped with a self
11 compactor or an industrial roll-off hoist and roll-off
12 container, used exclusively for garbage, refuse, or
13 recycling operations, may, when laden, transmit upon the
14 road surface, except when on part of the National System of
15 Interstate and Defense Highways, the following maximum
16 weights: 22,000 pounds on a single axle; 40,000 pounds on a
17 tandem axle; 40,000 pounds gross weight on a 2-axle
18 vehicle; 54,000 pounds gross weight on a 3-axle vehicle.
19 This vehicle is not subject to the bridge formula.

20 (7.5) A 3-axle rear discharge truck mixer registered as
21 a Special Hauling Vehicle, used exclusively for the mixing
22 and transportation of concrete in the plastic state, may,
23 when laden, transmit upon the road surface, except when on
24 part of the National System of Interstate and Defense
25 Highways, the following maximum weights: 22,000 pounds on
26 single axle; 40,000 pounds on a tandem axle; 54,000 pounds

1 gross weight on a 3-axle vehicle. This vehicle is not
2 subject to the bridge formula.

3 (8) Except as provided in paragraph (7.5) of this
4 subsection (a), tandem ~~Tandem~~ axles on a 3-axle truck
5 registered as a Special Hauling Vehicle, manufactured
6 prior to or in the model year of 2014 and first registered
7 in Illinois prior to January 1, 2015, with a distance
8 greater than 72 inches but not more than 96 inches between
9 any series of 2 axles, is allowed a combined weight on the
10 series not to exceed 36,000 pounds and neither axle of the
11 series may exceed 20,000 pounds. Any vehicle of this type
12 manufactured after the model year of 2014 or first
13 registered in Illinois after December 31, 2014 may not
14 exceed a combined weight of 34,000 pounds through the
15 series of 2 axles and neither axle of the series may exceed
16 20,000 pounds.

17 A 3-axle combination sewer cleaning jetting vacuum
18 truck registered as a Special Hauling Vehicle, used
19 exclusively for the transportation of non-hazardous solid
20 waste, manufactured before or in the model year of 2014,
21 first registered in Illinois before January 1, 2015, may,
22 when laden, transmit upon the road surface, except when on
23 part of the National System of Interstate and Defense
24 Highways, the following maximum weights: 22,000 pounds on a
25 single axle; 40,000 pounds on a tandem axle; 54,000 pounds
26 gross weight on a 3-axle vehicle. This vehicle is not

1 subject to the bridge formula.

2 (9) A 4-axle truck mixer registered as a Special
3 Hauling Vehicle, used exclusively for the mixing and
4 transportation of concrete in the plastic state,
5 ~~manufactured before or in the model year of 2014, first~~
6 ~~registered in Illinois before January 1, 2015,~~ and not
7 operated on a highway that is part of the National System
8 of Interstate Highways, is allowed the following maximum
9 weights: 20,000 pounds on any single axle; 36,000 pounds on
10 a series of axles greater than 72 inches but not more than
11 96 inches; and 34,000 pounds on any series of 2 axles
12 greater than 40 inches but not more than 72 inches. The
13 gross weight of this vehicle may not exceed the weights
14 allowed by the bridge formula for 4 axles. The bridge
15 formula does not apply to any series of 3 axles while the
16 vehicle is transporting concrete in the plastic state, but
17 no axle or tandem axle of the series may exceed the maximum
18 weight permitted under this paragraph (9) of subsection
19 (a).

20 (10) Combinations of vehicles, registered as Special
21 Hauling Vehicles that include a semitrailer manufactured
22 prior to or in the model year of 2014, and registered in
23 Illinois prior to January 1, 2015, having 5 axles with a
24 distance of 42 feet or less between extreme axles, may not
25 exceed the following maximum weights: 20,000 pounds on a
26 single axle; 34,000 pounds on a tandem axle; and 72,000

1 pounds gross weight. This combination of vehicles is not
2 subject to the bridge formula. For all those combinations
3 of vehicles that include a semitrailer manufactured after
4 the effective date of P.A. 92-0417, the overall distance
5 between the first and last axles of the 2 sets of tandems
6 must be 18 feet 6 inches or more. Any combination of
7 vehicles that has had its cargo container replaced in its
8 entirety after December 31, 2014 may not exceed the weights
9 allowed by the bridge formula.

10 (11) The maximum weight allowed on a vehicle with
11 crawler type tracks is 40,000 pounds.

12 (12) A combination of vehicles, including a tow truck
13 and a disabled vehicle or disabled combination of vehicles,
14 that exceeds the weight restriction imposed by this Code,
15 may be operated on a public highway in this State provided
16 that neither the disabled vehicle nor any vehicle being
17 towed nor the tow truck itself shall exceed the weight
18 limitations permitted under this Chapter. During the
19 towing operation, neither the tow truck nor the vehicle
20 combination shall exceed 24,000 pounds on a single rear
21 axle and 44,000 pounds on a tandem rear axle, provided the
22 towing vehicle:

23 (i) is specifically designed as a tow truck having
24 a gross vehicle weight rating of at least 18,000 pounds
25 and is equipped with air brakes, provided that air
26 brakes are required only if the towing vehicle is

1 towing a vehicle, semitrailer, or tractor-trailer
2 combination that is equipped with air brakes;

3 (ii) is equipped with flashing, rotating, or
4 oscillating amber lights, visible for at least 500 feet
5 in all directions;

6 (iii) is capable of utilizing the lighting and
7 braking systems of the disabled vehicle or combination
8 of vehicles; and

9 (iv) does not engage in a tow exceeding 20 miles
10 from the initial point of wreck or disablement. Any
11 additional movement of the vehicles may occur only upon
12 issuance of authorization for that movement under the
13 provisions of Sections 15-301 through 15-319 of this
14 Code. The towing vehicle, however, may tow any disabled
15 vehicle to a point where repairs are actually to occur.
16 This movement shall be valid only on State routes. The
17 tower must abide by posted bridge weight limits.

18 Gross weight limits shall not apply to the combination of
19 the tow truck and vehicles being towed. The tow truck license
20 plate must cover the operating empty weight of the tow truck
21 only. The weight of each vehicle being towed shall be covered
22 by a valid license plate issued to the owner or operator of the
23 vehicle being towed and displayed on that vehicle. If no valid
24 plate issued to the owner or operator of that vehicle is
25 displayed on that vehicle, or the plate displayed on that
26 vehicle does not cover the weight of the vehicle, the weight of

1 the vehicle shall be covered by the third tow truck plate
2 issued to the owner or operator of the tow truck and
3 temporarily affixed to the vehicle being towed. If a roll-back
4 carrier is registered and being used as a tow truck, however,
5 the license plate or plates for the tow truck must cover the
6 gross vehicle weight, including any load carried on the bed of
7 the roll-back carrier.

8 The Department may by rule or regulation prescribe
9 additional requirements. However, nothing in this Code shall
10 prohibit a tow truck under instructions of a police officer
11 from legally clearing a disabled vehicle, that may be in
12 violation of weight limitations of this Chapter, from the
13 roadway to the berm or shoulder of the highway. If in the
14 opinion of the police officer that location is unsafe, the
15 officer is authorized to have the disabled vehicle towed to the
16 nearest place of safety.

17 For the purpose of this subsection, gross vehicle weight
18 rating, or GVWR, means the value specified by the manufacturer
19 as the loaded weight of the tow truck.

20 (b) As used in this Section, "recycling haul" or "recycling
21 operation" means the hauling of non-hazardous, non-special,
22 non-putrescible materials, such as paper, glass, cans, or
23 plastic, for subsequent use in the secondary materials market.

24 (c) No vehicle or combination of vehicles equipped with
25 pneumatic tires shall be operated, unladen or with load, upon
26 the highways of this State in violation of the provisions of

1 any permit issued under the provisions of Sections 15-301
2 through 15-319 of this Chapter.

3 (d) No vehicle or combination of vehicles equipped with
4 other than pneumatic tires may be operated, unladen or with
5 load, upon the highways of this State when the gross weight on
6 the road surface through any wheel exceeds 800 pounds per inch
7 width of tire tread or when the gross weight on the road
8 surface through any axle exceeds 16,000 pounds.

9 (e) No person shall operate a vehicle or combination of
10 vehicles over a bridge or other elevated structure constituting
11 part of a highway with a gross weight that is greater than the
12 maximum weight permitted by the Department, when the structure
13 is sign posted as provided in this Section.

14 (f) The Department upon request from any local authority
15 shall, or upon its own initiative may, conduct an investigation
16 of any bridge or other elevated structure constituting a part
17 of a highway, and if it finds that the structure cannot with
18 safety to itself withstand the weight of vehicles otherwise
19 permissible under this Code the Department shall determine and
20 declare the maximum weight of vehicles that the structures can
21 withstand, and shall cause or permit suitable signs stating
22 maximum weight to be erected and maintained before each end of
23 the structure. No person shall operate a vehicle or combination
24 of vehicles over any structure with a gross weight that is
25 greater than the posted maximum weight.

26 (g) Upon the trial of any person charged with a violation

1 of subsection (e) or (f) of this Section, proof of the
2 determination of the maximum allowable weight by the Department
3 and the existence of the signs, constitutes conclusive evidence
4 of the maximum weight that can be maintained with safety to the
5 bridge or structure.

6 (Source: P.A. 96-34, eff. 1-1-10; 96-37, eff. 7-13-09; 97-201,
7 eff. 1-1-12.)

8 Section 99. Effective date. This Act takes effect upon
9 becoming law.